

Dialogic® System Release 6.0 PCI for Windows® (System Release 6.0 PCI Windows) enables higher density solutions with increased usability and flexibility. This release includes support for several new and enhanced media and signaling products. The installation, configuration, and diagnostic capabilities have been significantly enhanced which gives users greater control and flexibility. Additional details can be found in the [Dialogic® System Release 6.0 PCI for Windows® Release Update](#).

Features	Benefits
Continuous Speech Processing (CSP) operations including echo cancellation, voice energy detection, barge-in, voice event signaling, pre-speech buffering, and full-duplex operation	Enables development of high-quality, robust host-based Automatic Speech Recognition (ASR) applications
IP Media Library (IPML) API enhancements for support of RFC 2833, T.38 fax	Allows VoIP applications using IP signaling stacks other than those provided with Dialogic® products to use this library for application development
Learn Mode and Tone Set APIs are now supported on Dialogic® DM3 Media Boards	Supports detection of call progress tones and the modification of generated tones
Enhancements to Dialogic® Configuration Manager (DCM)	Improves configuration of individual boards, ports, and all associated parameters
SendAlive API and SRL event processing	Enables monitoring of the host computer for a failure and taking boards out of service to prevent the network from offering calls to a failed board or system

Operating Systems Supported

Details regarding supported operating systems can be found at
http://www.dialogic.com/~media/products/docs/appnotes/9861_SW_OS_Prod_Guide_an.pdf

Supported Products

Category	Boards and Gateways
Voice with Conferencing + Speech + Fax	DMV1200BTEPE, DMV600BTEPE, DMV300BTEPE, DMV600BTEP, DMV1200BTEP, DMV3600BP
Voice with Conferencing + Speech + Station	DI0408LS, DISI16, DISI24, DISI32
Voice with Speech + Fax	D/41JCT-LS, D/120JCT-LS, D/160JCT, D/240JCT-T1, D/300JCT-E1, D/320JCT, D/480JCT-1T1, D/480JCT-2T1, D/600JCT-1E1, D/600JCT-2E1, DMV160LP
Voice with Speech	D/4PCIU4S
Voice with Fax	D/4PCIUF, VFX/41JCT-LS
Voice	DM/V960-4T1, DM/V1200-4E1
Digital Interface	DM/N960-4T1, DM/N1200-4E1
IP	DM/IP241-1T1-100BT, DM/IP301-1E1-100BT, DM/IP481-2T1-100BT, DM/IP601-2E1-100BT
High Density Station Interface	HDSI/480, HDSI/720, HDSI/960, HDSI/1200
PBX Integration	D/42JCT-U, D/82JCT-U



www.dialogic.com

Dialogic Inc.
1504 McCarthy Boulevard
Milpitas, CA 95035-7405
USA

Dialogic is a registered trademark of Dialogic Inc. and its affiliates or subsidiaries ("Dialogic"). Dialogic's trademarks may be used publicly only with permission from Dialogic. Such permission may only be granted by Dialogic's legal department at the address provided above. The names of actual companies and products mentioned herein are the trademarks of their respective owners.

Dialogic encourages all users of its products to procure all necessary intellectual property licenses required to implement their concepts or applications, which licenses may vary from country to country. None of the information provided herein forms part of the specifications of the product(s) and any benefits specified are not guaranteed. No licenses or warranties of any kind are provided hereunder.

Any use case(s) shown and/or described herein represent one or more examples of the various ways, scenarios or environments in which Dialogic® products can be used. Such use case(s) are non-limiting and do not represent recommendations of Dialogic as to whether or how to use Dialogic products.

Dialogic may make changes to specification, product descriptions, and plans at any time, without notice.